

WIRE CLOTH SPECS

Mesh	Wire Diameter	Opening	Open Area (%)
6 X 6	0.0350	0.1320	62.70
8 X 8	0.0170	0.1060	74.60
8 X 8	0.0230	0.1020	65.20
10 X 10	0.0250	0.0750	56.30
12 X 12	0.0230	0.0600	51.60
16 X 16	0.0180	0.0450	50.70
20 X 20	0.0140	0.0360	51.80
20 X 20	0.0160	0.0340	46.20
30 X 30	0.0110	0.0220	44.80
40 X 36	0.0110	0.0150/ 0.0190	39.20
50 X 40	0.0080	0.0120/ 0.0170	41.10
60 X 50	0.0065	0.0100/ 0.0130	41.20
60 X 50	0.0075	0.0090/ 0.0130	34.80
80 X 70	0.0055	0.0070/ 0.0090	32.60
100 X 90	0.0045	0.0060/ 0.0070	30.20
120 X 108	0.0035	0.0050/ 0.0060	32.30
150 X 140	0.0025	0.0041/ 0.0042	36.10
200 X 190	0.0021	0.0029/ 0.0033	34.10

WIRE CLOTH (S.S) - MICRON COMPARISON

Mesh	Micron Retention
50 X 250	63
50 X 250 - Twin Warp	45
165 X 800	26
165 X 1400	15
200 X 1400	10